

## Flexi Screen Ultra / Guard

Extraordinarily Effective and Classic Design



**DECONIK**  
COMMERCIAL  
GROUP



**DECONIK**  
COMMERCIAL  
GROUP

## Flexi Screen Ultra / Guard

Extraordinarily Effective and Classic Design

### Functionality:

Deconik provides a high-density, portable, and easy-to-read assembly panel called flexi screen lite.

The features of this panel include high density polyurethane foam, which helps to maximize absorption efficiency. The panel surrounds the microphone with clear sound at low and intermediate frequencies.

This panel has dual functionality. The inner surface, the frequency absorption, and the bass of the reader's sound, while the external surface of the panel, absorbs reflections scattered in the room.

The structure of the foam has a good density and thickness. By designing the cavities, the joint mechanism has enhanced the absorption and reflection control effect.

This panel is suitable for a wide range of microphones. This panel can be assembled in less than 30 seconds. It can be used for all recording sites, studios, schools, conference halls, etc.



MADE IN IRAN

**12 MONTHS Warranty**  
DECONIK Company

This product includes a warranty of 12 months.

[Deconik Warranty Terms](#)

1. Products made of polyurethane foam changes such as perforation, cut or deformation caused by heat, chemicals, high pressure and dust is out of warranty terms.
2. Do not place the product in direct sunlight. Otherwise, the product has no warranty.
3. Polyurethane products are flammable. Do not place them near flammable materials.

**Operation**  
ABSORPTION

**Materials**  
FOAM & MDF  
& WOOD

**Color**  
BLACK  
YELLOW  
WITHE

**MODEL** FLEXI SCREEN Guard

FLEXI SCREEN ULTRA



[www.Deconik.net](http://www.Deconik.net)



## Installation guide

Connect the pieces of the product according to the map

### ① MDF- WOOD

The back page  
Colored veneer

### ② Foam

Absorber shield

### ③ Nut

### ④ screw

### ⑤ the keeper

### ⑦ Tripod

## FLEXI SCREEN

### Ultra / Guard

Microphone Absorber shield

Flexi screen has a dual functionality, absorbing the singers energy on the inside to give a less ambient sound, while at the same time, partially absorbing scattered room reflections on the outside. flexi screen acoustic foam structural support to the joint mechanism.

flexi screen is suitable for use with a range of microphones and can be adjusted either vertically or horizontally. the unit can be assembled in less than 15 seconds making it ideal for location-based recording venues.

project studios and classrooms

**size**  
51 - 34 - 33 CM

**Materials**  
FOAM

**Operation**  
ABSORPTION

**Color**  
01  
02



[www.Deconik.net](http://www.Deconik.net)



This product includes a warranty of 12 months.

### Deconik Warranty Terms

1. Products made of polyurethane foam changes such as perforation, cut or deformation caused by heat, chemicals, high pressure and dust is out of warranty terms.
2. Do not place the product in direct sunlight. Otherwise, the product has no warranty.
3. Polyurethane products are flammable. Do not place them near flammable materials.

### Install Steps

1. The back panel, near the sides with adhesive Patks, aquarium, belt or not impregnated polyurethane.
2. With the installation, check the appropriate size and angle.
3. Clean the surface of the back panel is not bulge.
4. keep the panel 1 to 5 minutes on the installation place to dry glue.



**WARNING:**  
THIS PRODUCT IS FLAMMABLE

DECONIK COMPANY  
ACOUSTIC PANEL PRODUCTION



[www.Deconik.net](http://www.Deconik.net)

